



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB290

Excavator

STANDARD EQUIPMENT

Operating Weight: 18,780 lbs. Width: 7' 7" Maximum Dig Depth: 15' Bucket Digging Force: 16,565 lbs. Net Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 26.4 gpm / 14.5 gpm Boom Swing: Left 70° / Right 60° Track Width: 17.7" Rubber / 21.7" Steel	ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet, and AM/FM/MP3 radio Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Load sensing variable displacement hydraulic system Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights
Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Automatic track tensioner Auto Idle	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB290C	TB290 Cab Equipped with Rubber or Steel Tracks	\$110,500
TB290CA (w/ Angle Blade)	TB290 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$116,500
TB290CL (w/ Road Liner Tracks)	TB290 Cab (above Equipped except with Road Liner Tracks)	\$116,290
TB290CLA (w/ Angle Blade & Road Liner Tracks)	TB290 Cab (above Equipped except with Road Liner Tracks) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$122,290

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH0701	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH070K	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435



TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

Zero Swing Excavator

STANDARD EQUIPMENT

Operating Weight: 19,077 lbs. Width: 7' 7" Maximum Dig Depth: 14' 11" Bucket Digging Force: 16,335 lbs. Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 39 gpm / 15 gpm Boom swing: Left 30° / Right 15° Track Width: 17.7"	ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio Tilt-up operator's platform Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable displacement axial piston main hydraulic pumps Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights
Side-to-Side (STS) offset boom system Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto idle	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB280FRC	TB280FR Cab Equipped with Rubber or Steel Tracks	\$114,000
TB280FRCL (w/ Road Liner Tracks)	TB280FR Cab Equipped with Road Liner Tracks	\$119,790

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036 *	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036 *	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D *	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH070I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2" belt	\$91
BTH070K *	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435

* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)



519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

TB1140

SERIES 2

Excavator

STANDARD EQUIPMENT

Operating Weight: 34,700 lbs. (Steel)	Factory installed cab with auto air conditioner/heat/defroster, AM/FM/MP3 radio, wiper
Dozer Blade Width: 8' 6"	Air suspension seat
Maximum Dig Depth: 18' 0"	Two speed travel with automatic shift down
Bucket Digging Force: 22,188 lbs.	Travel alarm
Tail Swing Radius: 6' 9"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 103.3 / 2,000	Control pattern selector valve
EPA Interim Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.3 mph	Wrap around counterweight
Auxiliary Flow: (Primary) 59 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
Boom swing: Left 77° / Right 53°	Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only)
24" Wide Steel Tracks	Proportional thumb control of both auxiliary hydraulic circuits
Optional: 20" Rubber Track	Variable displacement axial piston main hydraulic pumps
Optional: 20" Road Liner style tracks	LCD gauge panel with multi-function operator information center
	Heavy duty dozer blade with Float
	Accumulator

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB1140	TB1140 Equipped with CAB, Rubber or Steel Tracks, Dozer blade with float, Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer, Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio, Air Suspension seat, Engine monitoring system	\$160,395
TB1140CL (w/ Road Liner Tracks)	TB1140 Cab (above Equipped except with Road Liner Tracks)	\$169,343

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BMC1140	Mechanical Coupler: Pin Grabber type with Pins (700 lbs)	\$5,130
BTB114018	18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$2,745
BTB114024	24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$2,825
BTB114030	30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$3,385
BTB114036	36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$3,660
BTB114042D	42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$2,708
BTB114048D	48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$2,915
BTB114054D	54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,130
BTB114060D	60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$3,335
BTH1140I	INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)	\$7,765
BTH1140LI	INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler)	\$7,765

FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2"	\$123
BTH1140K	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)	\$7,305
BTH1140LK	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler)	\$7,305
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482